

Job Name:

Contact:

Ordering Code:

Fixture Type:



Uno, Duo, Quattro

Description

- Round LED aluminum semi-recessed spotlight
- Matte chrome or chrome finish
- 1, 2 or 4 light points
- Optional 2" J-box

Mounting

- Line voltage:
- 2-1/4" hole cutout
 - 3/16" - 1-1/16" required material thickness
- Low voltage:
- 1-3/8" hole cutout
 - 1/2" required material thickness

Electrical / LED Driver

- Line voltage:
- 120-240Vac input, 50/60Hz, 5VA, 3W
 - For dimming options consult factory
- Low voltage:
- 3Vdc, 500mA constant current, 1.5W (remote driver required)

Listings

- ETLus Listed to UL1598 and UL2108 (suitable for dry locations only)
- cETL Listed to CSA C22.2 #250.0
- IP54 rated




Ordering Codes

Follow the steps to specify your fixture, example: 135 - 20 - 5 - 5 - ch


Part Number	Cover Light Points	Mounting	CCT	Finish
135 LED	20 uno, 1 x 120° beam	5 ¹ with j-box and driver	amb amber	ch Chrome
	22 duo, 2 x 120° beam	1 ² without j-box and driver	3 3000K	mc Matte Chrome
	21 quattro, 4 x 20° beam		5 5000K	

Notes


1. J-Box is not for use with through wiring
2. Remote driver required




1 x 120° beam



2 x 120° beam



4 x 20° beam



with j-box and driver

Job Name:

Contact:

Ordering Code:

Fixture Type:

LED Performance

LED	Cree XPG	Lumen			
		Light Points	Amber	3000K	5000K
DUV	.001				
CCT	Amber (590-595nm), 3000 or 5000K	1	6 lm	49 lm	52 lm
CRI Ra	>80	2	11 lm	80 lm	91 lm
Life	L90 51,000 hrs.	4	23 lm	49 lm	52 lm
Warranty	5 year limited warranty				

Driver Matrix

Driver	Quantity	Power Spec
P70418-500	26W LED Driver w/ box for 2-16 fixtures	120-277V, 26W, 500mA, Trailing Edge (ELV) dimming
P70414-500-ECO	50W LED Driver w/ box for 1-15 fixtures per channel (1 channel driver)	120-277V, 50W, 500mA, 0-10V (1%) dimming
P70414-500-SOLO	50W LED Driver w/ box for 1-15 fixtures per channel (2 channel driver)	120-277V, 50W, 500mA, 0-10V (.1%) dimming
P70469-500-ECO	50W LED Driver w/ box for 1-15 fixtures per channel (1 channel driver)	120-277V, 50W, 500mA, DALI (1%) dimming
P70469-500-SOLO	50W LED Driver w/ box for 1-15 fixtures per channel (2 channel driver)	120-277V, 50W, 500mA, DALI (.1%) dimming
P70470-500	50W LED Driver w/ box for 1-10 fixtures per channel (3 channel driver)	120-277V, 50W, 500mA, DMX/ ROM (0%) dimming