CONTACT -



ORDERING CODE

Direct Wall



DESCRIPTION

Glaz is a decorative sconce with warmly illuminated opal glass. It has a cubical form factor and is ADA compliant. Glaz mounts to a standard 4" junction box with a white finish canopy.

HOUSING

Triplex layered glass.

MOUNTING

Square base over a 3-1/2" to 4" recessed round junction box.

ELECTRICAL/CONTROLS

- Dimmer: Lutron DVELV-300P

LISTINGS

- ETLus Listed to UL1598 (suitable for dry locations only)
- cETL Listed to CSA C22.2 #250.0
- ADA Compliant

LED INFO

- LED: Zigen ZGIBGX30KHO
- SDCM: 3-step MacAdam Ellipse
 Lumen Maintenance: L₇₀ > 50,000 hrs
 Warranty: 5 year limited warranty

ODDEDI	NC COD	-
ORDERI	NG CODI	=




ADA | M-79

	OKDEKING CO	JUE	LIVI 70
1	SERIES	WALL	indoor wall sconce
]	TYPE	GLA	Glaz up and down, 9.2W, 330lm up, 330lm down
	сст	30K 35K	3000K 3500K
	CRI	90	90 CRI
	VOLTAGE	UNV	120V-277V
	DIMMING	ELV ¹	trailing edge dimming to 5%
	FINISH	WH	white glass



Follow the steps to specify your fixture, example: WALL - GLA - 30K - 90 - UNV - ELV - WH

NOTES
1. ELV only available at 120V.



Page 1 of 1