

## JAZZ ACOUSTIC

Surface Round



### FEATURES

- 40" Recycled PET fiber acoustic panel
- High sound adsorption capability
- UV and dimensionally stable
- Harmless low VOC emissions textile
- Direct and Indirect light outputs
- Three color options for canopy and acoustic finish available

### ELECTRICAL/CONTROLS

- 120-277Vac, 50/60Hz input
- 0-10V Dimming to 1.0%

### LISTING

- IP20 rating
- ETLus Listed to UL1598 (suitable for indoor use and dry locations only)
- cETL Listed to CSA C22.2 #250.0

### LED INFO

- SAMSUNG LM281B+ LED: CRI: >90, SDCM: 3-step MacAdam Ellipse, Lumen Maintenance: L<sub>80</sub> > 50,000 hrs

PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

### ORDERING CODE

<b>SERIES</b>	JAZZ-S	jazz surface
<b>TYPE</b>	RD	round
<b>SIZE</b>	16/40	D16" jazz / D40" outer acoustic
	24/40	D24" jazz / D40" outer acoustic
<b>LIGHT OUTPUT</b>	D	direct only
	DI	direct/indirect
	Leave blank if acoustic element chosen	
<b>CURRENT</b>	500	500mA
	700	700mA
	900	900mA
	Leave blank if acoustic element chosen	
<b>CCT</b>	27K	2700K
	30K	3000K
	35K	3500K
	40K	4000K
	Leave blank if acoustic element chosen	
<b>CRI</b>	90	90 CRI
	Leave blank if acoustic element chosen	
<b>ACOUSTIC FINISH</b>	ACTAN	acoustic anthracite
	ACTWH	acoustic white
	ACTGY	acoustic grey
<b>DIMMING</b>	UNV-DIM10	120V-277V integrated driver, flicker free 0-10V dimming to 1%
	Leave blank if acoustic element chosen	

### ORDERING CODE

Follow the steps to specify your fixture, example:  
**JAZZ - S - RD - 24/40 - D - 700 - 30K - 90 - ACTAN - UNV - DIM10**

DIRECT (3000K)			
SIZE	500mA	700mA	900mA
16"	1100lm / 11W	1530lm / 15W	1960lm / 19W
24"	2580lm / 24W	3570lm / 31W	4580lm / 39W

INDIRECT (3000K)			
SIZE	500mA	700mA	900mA
16"	408lm / 4W	564lm / 5W	724lm / 5W
24"	816lm / 5W	1128lm / 8W	1448lm / 10W

### COLOR OPTIONS

#### ACOUSTIC FINISH



Anthracite  
ACTAN

White  
ACTWH

Grey  
ACTGY

PROJECT INFORMATION

JOB NAME		TYPE	
ORDERING CODE			

PRODUCT DIMENSIONS

