


## KADO

### Tiltable Recessed Spotlight



#### DESCRIPTION

- Tiltable LED recessed spotlight
- Matte chrome or chrome finish
- 50° tilt, 12° or 30° faceted lenses

#### MOUNTING

- Low Voltage**
- 1 3/8" hole cutout
- 3/8" required material thickness

#### ELECTRICAL

- Low Voltage**
- 3.2Vdc, 500mA constant current, 1.6W (remote driver required)

#### LISTING

- ETLus Listed to UL2108 (suitable for dry locations only)
- cETL Listed to CSA C22.2 #9.0
- IP20 rated

#### LED PERFORMANCE

- LED:** Cree XPG
- SDCM:** 3 Step MacAdam Ellipse
- CCT:** 3000K
- CRI:** >80
- Life:** L<sub>70</sub> 51,000hrs

#### PROJECT INFORMATION


JOB NAME		TYPE	
ORDERING CODE			

#### ORDERING CODES

PART NUMBER	FEATURES	DEGREE	KELVIN	LUMENS
56-6126	chrome	12°	3000	126
56-6026	matte chrome	12°	3000	126
56-6127	chrome	30°	3000	126
56-6027	matte chrome	30°	3000	126



12°



30°

#### DRIVER MATRIX

PART NUMBER	DRIVER	QUANTITY	POWER SPEC
P70418-500	32W LED Driver w/ box	for 7-14 fixtures	120-277V, 32W, 500mA, Trailing Edge (ELV) 1% dimming
P70414-500-ECO	50W LED Driver w/ box	for 1-16 fixtures per channel (1 channel driver)	120-277V, 50W, 500mA, 0-10V (1%) dimming
P70414-500-SOLO	50W LED Driver w/ box	for 1-16 fixtures per channel (2 channel driver)	120-277V, 50W, 500mA, 0-10V (.1%) dimming