

CONTACT ORDERING CODE



# **Indirect** Wall/Ceiling







Runner is an indirect, linear, surface mount for wall or ceiling. It delivers even illumination on the surface and is offered in 16" and 36" lengths with a white finish. It includes a flush mount field paintable junction box cover.

### HOUSING

Extruded aluminum housing with white finish.

### MOUNTING

Mount to 3-1/2" to 4" octagonal or 4" square recessed junction box.

## **ELECTRICAL/CONTROLS**

- Dimmer: Lutron DVSTV-WH Diva 0-10 V Control

- ETLus Listed to UL1598 (suitable for dry and damp locations)
- cETL Listed to CSA C22.2 #250.0
- ADA Compliant

## **LED INFO**

- LED: Edison SMD LED Strip

- Lumen Maintenance: L<sub>70</sub> > 50,000 hrs
- Warranty: 5 year limited warranty

## ORDERING CODE




ADA LM-79

SREEKING COEL		
SERIES	WALL	indoor wall sconce
TYPE	RUN1 RUN2	Runner indirect 16", 22W, 2000 Im Runner indirect 36", 42W, 4000 Im
сст	30K	3000K
CRI	90	90 CRI
VOLTAGE	UNV	120V-277V
DIMMING	10V	0-10V dimming to 10%
FINISH	WH	white

## ORDERING CODE

Follow the steps to specify your fixture, example: WALL - RUN1 - 30K - 90 - UNV - 10V - WH





Runner 36'

