

Light efficiency:

50 Lumen/Watt

Light quality:

CRI: 80.7

Color temperature:


4038 K

Output: 620 lm

Peak: 2060 cd


Power: 12.5 W

PF: 0.91




EXT-SKY-D-SW-10LM-40K-80-E-24-BK-BK

Date and time:
11/2/2021 9:29:47 AM






CIE 1931
x: 0.380
y: 0.378

Spectra





Power





TM30: 81.7

CRI: 80.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
79.6	84.3	88.1	82.1	79.4	78.9	85.7	67.1	10.3	62.9	81.3	61.8	80.1	93.1	73.4


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
81.3	82.2	72.4	78.5	83.6	87.0	88.0	86.5	87.2	78.3	76.7	76.2	85.8	86.8	80.1	80.2

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
80.4	96.5	76.3	76.0	80.8	80.6	82.3	88.7	95.1	83.4	81.5	81.8	82.7	71.7	74.9

CQS: 81.0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
4038 K	80.7	10.3	81.7	98.7	81.0	0.380	0.378	0.224	0.335	0.0010







Rf 81.7


Fidelity index Rf

Rg 98.7

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	81	-11%	-3%
2	82	-8%	6%
3	72	-4%	15%
4	78	4%	13%
5	84	9%	8%
6	87	9%	-2%
7	88	2%	-8%
8	86	-4%	-7%
9	87	-8%	-3%
10	78	-11%	7%
11	77	-2%	15%
12	76	5%	12%
13	86	9%	0%
14	87	9%	-4%
15	80	2%	-15%
16	80	-4%	-13%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2058lx	514lx	229lx	129lx	82lx	57lx	42lx	32lx	25lx	21lx	17lx	14lx	12lx	10lx	9lx	8lx	7lx	6lx	6lx	5lx
191.2fcd	47.8fcd	21.2fcd	11.9fcd	7.6fcd	5.3fcd	3.9fcd	3fcd	2.4fcd	1.9fcd	1.6fcd	1.3fcd	1.1fcd	1fcd	0.8fcd	0.7fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2058	2045	2010	1959	1892	1805	1700	1565	1408	1243	1068	905	762	629	514	414	328	257	199	152
100%	99%	98%	95%	92%	88%	83%	76%	68%	60%	52%	44%	37%	31%	25%	20%	16%	12%	10%	7%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2058	1997	1820	1523	1177	879	654	496	388	310	252	212	181	152	121	92	71	55	43	33
100%	97%	88%	74%	57%	43%	32%	24%	19%	15%	12%	10%	9%	7%	6%	4%	3%	3%	2%	2%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2058	2045	2010	1959	1892	1805	1700	1565	1408	1243	1068	905	762	629	514	414	328	257	199	152
100%	99%	98%	95%	92%	88%	83%	76%	68%	60%	52%	44%	37%	31%	25%	20%	16%	12%	10%	7%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2058	1997	1820	1523	1177	879	654	496	388	310	252	212	181	152	121	92	71	55	43	33
100%	97%	88%	74%	57%	43%	32%	24%	19%	15%	12%	10%	9%	7%	6%	4%	3%	3%	2%	2%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
{B_ANG}°	53.9°	76.9°	99.2%	98.3%