

## LUPE

Wall SW WD E26

WE PLIGHT  
COLLECTION



### FEATURES

- Designed, handcrafted, and painted by Master Artisans
- Made to order, eliminating waste
- 6 wood stains + 11 colors to mix & match
- Traditional E26 socket or range of LED options. 3000K, 3500K, & Warm Dim 3000K, dim to 1800K

### HOUSING

- Composed of recycled, locally sourced reconstructed wood veneer
- USA factory assembled shades with some exceptions due to size
- Due to hand-crafted nature, colors may vary from fixture to fixture and from photo

### MOUNTING

- Wall mounted to recessed junction box

### LISTING

- ULus listed to UL1598 (suitable for indoor use and dry locations only)
- cUL listed to CSA C22.2 #250.0

#### CCT AT LIGHT LEVEL (%LF) FOR WARM DIM LED

%LF	CCT
100%	3000
50%	2800
25%	2300
10%	1900
5%	1800

PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

### ORDERING CODE

SERIES	WEP	wood shade
TYPE	LUP	lupe
SIZE	60	60 sconce, 2 x light source
LIGHT SOURCE	LE26 <sup>1</sup> LLED	E26 socket LED
CCT	30K 35K 3018	3000K standard white LED 3500K standard white LED 3000K warm dim LED, to 1800K <small>Not applicable to LE26 option. Do not include in LE26 ordering code.</small>
CRI	90 <sup>2</sup> 95 <sup>3</sup>	90 CRI, standard white 95 CRI, warm dim <small>Not applicable to LE26 option. Do not include in LE26 ordering code.</small>
MOUNTING OPTION	W	wall mount
OUTER SHADE COLOR	ASH BCH BLU EBY GRN GYO OCH PGR PTB RED ROS TRC WHT WNG YLW LPT VLT	ash beech blue ebony green grey oak ocher pale green petiribi red rose teracotta white wenge yellow light petrol violet
INNER SHADE COLOR	ASH BCH BLU EBY GRN GYO OCH PGR PTB RED ROS TRC WHT WNG YLW LPT VLT	ash beech blue ebony green grey oak ocher pale green petiribi red rose teracotta white wenge yellow light petrol violet

### ORDERING CODE

Follow the steps to specify your fixture, example:  
**WEP - LUP - 60 - LLED - 3018 - 95 - W - EBY - RED**

#### NOTES

1. 15W E26 socket available, use base option code LE26-15.
2. 90 CRI for standard white only.
3. 95 CRI for warm dimming only.

### COLOR OPTIONS



PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

## LIGHT SOURCE

Light Source	LLED - Standard White LED	LLED - Warm Dim LED	LE26 - E26 Socket
<b>Performance</b>			
LED	Cree CMT 1420	Luminus CDM-9	Lamp Dependant
Lumens	1300 lm	970 lm	
CCT	3000K or 3500K	3000K to 1800K	
SDCM	2-Step MacAdam Ellipse	3-Step MacAdam Ellipse	
CRI	>90	>95	
Lumen Maintenance	L <sub>90</sub> > 41,500 hours	L <sub>70</sub> > 54,000 hours	
<b>Technical Specs</b>			
Socket Listing	Integrated LED module ETLus Listed to UL1598 (Suitable for dry locations only) cETL Listed to CSA C22.2 #250.0	Integrated LED module ETLus Listed to UL1598 (Suitable for dry locations only) cETL Listed to CSA C22.2 #250.0	Medium E26 base socket ETLus Listed to UL1598 (Suitable for dry locations only) cETL Listed to CSA C22.2 #250.0
<b>Mounting</b>			
Wall	120-277Vac, 50/60Hz input 16W 0-10V Dimming to 10%	120-277Vac, 50/60Hz input 16W 0-10V Dimming to 10%	120Vac input 100W, 100VA (max 100W lamp) Dimmable (with compatible lamp)
<b>Warranty</b>			
	5 year limited fixture warranty	5 year limited fixture warranty	1 year limited fixture warranty

## MOUNTING OPTIONS

