
WEP Renata 200 OVL







ELECTRICAL KIT

1 x 2

x 2

0 0

₽ x 1

₽ x 1





Feed cord through ring.



Pull cord until socket bottoms out.



Pass lock washer and nut through cable.



Firmly tighten socket to shade ring.



Feed cord through canopy.




After adjusting cord length, tighten set screw on canopy.




Feed additional strain relief through cord.



Slide down until it bottoms out and tighten set screw.



Pass aircraft cable through one hole of strain relief.



Loop same end of aircraft cable through balancer.



Continue to feed aircraft through remaining opening of strain relief.



Tighten both screw of strain relief and adjust aircraft cable length as needed. Cut loose aircraft cable if necessary.



Same as step 12.

WARNING – PLEASE READ ALL INSTRUCTIONS PRIOR TO INSTALLATION. READ AND FOLLOW ALL WARNINGS AND INSTRUCTIONS BEFORE INSTALLING OR MAINTAINING THIS PRODUCT. TURN OFF POWER PRIOR TO ANY WORK ON THE SYSTEM OR PRODUCT. DO NOT INSTALL DAMAGED PRODUCT.

Installing, wiring, and maintenance must be done by qualified persons or a certified electrician in accordance with all local and National Electrical Codes.

Warranty is voided in case of unauthorized modifications and/or improper use.

Save these instructions and refer to them when additions, changes, or services to the fixture or system are made.

CAUTION - Do not install any fixture assembly closer than 6 inches (15.24cm) from any combustible material (insulation)

Refer to product label for voltage requirements and properly ground fixture in accordance with all local and national electrical codes.

Product will support dimming with compatible lamp and dimmer.

Suitable for dry locations.

DO NOT use chemicals or water to clean shade, ONLY use DRY cloth.

Must use suspension kit (p/n: K20263) when provided.

120 VAC input Max 100W lamp

♠ WARNING

Â

ADVERTENCIA

AVERTISSEMENT



- To avoid possible electrical shock, before installing light fixtures, disconnect power by turning off the circuit breakers both to the outlet box and to its associated wall switch location if you cannot lock the circuit breakers in the off position, securely fasten a prominent warning device, such as a tag to the service panel.
- Verify that supply voltage is correct by comparing it with the luminaire label information.
- Make all electrical and grounded connections in the accordance with the National Electrical Code (NEC) and any applicable local code requirements.
- Allow sufficient time for fixture and / or driver to cool before servicing and performing maintenance.

- Para evitar un posible choque, antes de instalar luminarias, desconecte la alimentación apagando los interruptores de
- circuito y ubicación del interruptor de pared. Si no se pueden bloquear los interruptores en la posición de apagado, sujetar un dispositivo de advertencia en el panel de servicio.
- Compruebe que la tensión de alimentación es correcta comparándola con la información de etiqueta de la luminaria.
- Hacer todas las conexiones eléctricas y puesta a tierra de acuerdo con el código eléctrico nacional (NEC) y los requisitos del código local aplicable.
- Permitir suficiente tiempo para el luminario y el controlador para enfriar antes de enpesar el servicios y mantenimiento.

Pour éviter les chocs, avant d'installer des appareils

- d'éclairage, coupez l'alimentation en désactivant les disjoncteurs et l'emplacement du commutateur mural. Si vous ne pouvez pas verrouiller les disjoncteurs en position d'arrêt, fixer un avertissement sur le panneau de service.
- Vérifiez que la tension d'alimentation est correcte en le comparant avec les informations d'étiquette de luminaire.
- Effectuer tous les raccordements électriques et mise à la terre dans la conformité avec le Code électrique National (NEC) et des exigencies du code local applicable.
- Laisser suffisamment de temps pour l'appareil et pilote refroidir avant d'effectuer l'entretien et la maintenance.

CAUTION





A A

MIS EN GARDE



- All wiring must be in accordance with national and local electrical codes and ANSI/NFPA 70. If you are unfamiliar with wiring you should use qualified electrician.
- PPE Personal Protective Equipment such as gloves and safety glasses should be used at all times when installing, maintaining or servicing.
- · Risk of fire. Keep combustible material away from fixtures.
- Todo el cableado debe hacerse de conformidad con los
- Todo el cableado debe hacerse de conformidad con los códigos eléctricos nacionales y locales y ANSI/NFPA 70. Si no está familiarizado con el cableado, se debe utilizar a un electricista.
- Equipo de protección personal como guantes y lentes de seguridad se debe utilizar al instalar, mantener o reparar.
- Riesgo de incendio. Mantenga los materiales combustibles lejos de los liminario.
- Tout le câblage doit être effectué conformément aux codes électriques locaux et nationaux et ANSI/NFPA 70. Si vous êtes peu familier avec câblage, vous devez utiliser un électricien
- Équipement de protection personnelle comme des gants et des lunettes de sécurité doivent être utilisé en tout temps lors de l'installation, maintenance ou entretien.
- Risque d'incendie. Garder les matières combustibles loin de luminaires.