

Z15

LED Pendant Cylinder Xicato

XICATO



DESCRIPTION

Z15 is a performance spot fixture in a par20 cylinder form factor integrated with industry best LEDs up to 1470 lm. Z15 has many options for most applications and carries the first 5 Year NO COLOR SHIFT AND FIXTURE WARRANTY.

HOUSING

Extruded aluminum housing with white, matte chrome or black finish

MOUNTING

- Pendants provided with 60" adjustable cord.
- Canopy over a 3-1/2" to 4" recessed octagonal junction box for P mounting option.
- Optional track mounting: Global Trac Systems, GEO track, ECO track / HALO® Power Trac track, and Zonyx track.

LISTINGS

- ETLus Listed to UL1598 (suitable for dry and damp locations)
- ETLus Listed to UL1574 (track suitable for dry locations only)
- cETL Listed to CSA C22.2 #250.0 and #9.0
- Made in the USA - meets the requirements of the Buy American provision within the ARRA

LED INFO

- XICATO XTM:
- SDCM = 1x2 MacAdam Ellipse, Duv +/- 0.001, Lumen Maintenance: L₉₀ > 55,000 hrs

PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

XICATO XTM MODULE - ORDERING CODES

PART NUMBER	112250	
LED	XTM19	XICATO XTM 19mm
DELIVERED LUMENS	11LM	835 lm
	13LM	950 lm
	16LM	1160 lm
	20LM ¹	1470 lm
	Standard Configuration: 3000K 83CRI SA20	
CCT	27K	2700K
	30K	3000K
	35K	3500K
	40K	4000K
CRI	83	83 CRI
	98	98 CRI
REFLECTOR & LUMEN MULTIPLIER	SSA20	20° semi-specular (0.92)
	SSA40	40° semi-specular (0.82)
	SSA60	60° semi-specular (0.93)
	SA20	20° specular (1.00)
	SA40	40° specular (1.00)
	SA60	60° specular (0.99)
	DA20	20° diffused (0.86)
	DA40	40° diffused (0.88)
	DA60	60° diffused (0.89)
	10° narrow beam angle, see page 2 for details.	
VOLTAGE	120 UNV	120V 120V-277V
DIMMING	ELV ² 10V ³	10% trailing edge dimming 0-10V dimming to 10% See Dimming Availability Chart at the bottom of this page for details.
FINISH	BK WH MC	black white matte chrome
MOUNTING OPTIONS	ECOBK ECOWH GEOBK GEOWH ZONMC P ECOMC GEOMC	ECO/HALO black ECO/HALO white GEO black GEO white Zonyx matte chrome pendant ECO/HALO matte chrome GEO matte chrome
LITE OPTICS	CLR	standard snoot / lens

ORDERING CODE

Follow the steps to specify your fixture, example:
112250 - XTM19 - 20LM - 35K - 83 - SSA20 - 120 - ELV - MC - ECOBK - CLR

XTM19 (LED)	POWER		DIMMING AVAILABILITY		
	DELIVERED LM	W (83 CRI)	W (98 CRI)	ELV	10V
835	13	14			
950	15	17			
1160	16	18			
1470	18	N/A			

Power Factor ≥ 0.9

	ELV	10V
11LM 83	•	
11LM 98	•	
13LM 83	•	•
13LM 98		•
16LM 83	•	•
16LM 98	•	•
20LM 83	•	•
20LM 98		

NOTES

1. 20LM not available in 98CRI.
2. ELV dimming only available in 120V.
3. 0-10V dimming only available in UNV voltage with P mount.

PROJECT INFORMATION		
JOB NAME		TYPE
ORDERING CODE		

10° NARROW BEAM - ORDERING CODES

PART NUMBER	112250	
LED	XTM09	XICATO XTM 9mm
DELIVERED LUMENS	12LM	900 lm
CCT	27K 30K 35K 40K	2700K 3000K 3500K 4000K
CRI	83	83 CRI
REFLECTOR	SA10	10° specular
VOLTAGE	120 UNV	120V 120V-277V
DIMMING	ELV ¹ 10V ²	10% trailing edge dimming 0-10V dimming to 10%
FINISH	BK WH MC	black white matte chrome
MOUNTING OPTIONS	P ECOBK ECOWH ECOMC GEOBK GEOWH GEOVC ZONMC	pendant ECO/HALO black ECO/HALO white ECO/HALO matte chrome GEO black GEO white GEO matte chrome Zonyx matte chrome
LITE OPTICS	CLR	standard snoot / lens

ORDERING CODE

Follow the steps to specify your fixture, example:

112250 - XTM09 - 12LM - 35K - 83 - SA10 - 120 - ELV - MC - ECOBK - CLR

XTM09 (LED)	POWER
DELIVERED LM	W (83 CRI)
900	16

Power Factor ≥ 0.9

NOTES

1. ELV dimming only available in 120V.
2. 0-10V dimming only available in UNV voltage with P mount.

PROJECT INFORMATION

JOB NAME		TYPE	
ORDERING CODE			

MOUNTING OPTIONS

Mounting Options

- P Pendant
- ECOBK ECO/HALO black
- ECOMC ECO/HALO matte chrome
- ECOWH ECO/HALO white
- GEOBK GEO black
- GEOHC GEO matte chrome
- GEOWH GEO silver
- ZONMC Zonyx matte chrome

