

JOB NAME _____

CONTACT _____

ORDERING CODE _____

ORDERING CODE



LM-79


SERIES	350	Zonyx
TYPE	004 006 006-1 008 008-1	4 ft track 6 ft track 5 ft factory curved track 8 ft track 7 ft factory curved track
VOLTAGE	120	120V
FINISH	MC	matte chrome

ZONYX

Zonyx Track



Follow the steps to specify your fixture, example:
350 - 004 - MC



DESCRIPTION

Zonyx is Bruck's decorative line voltage track system. It's field or factory bendable to 18" radius allowing versatility for demanding designs and installations. A low voltage system where the lighting is an element of the space design.

HOUSING

- sleek matte chrome anodized extruded aluminum construction

MOUNTING

- Suspension support
- Ceiling support
- Wall Support
- Canopy
- Stepdown uniplug adaptor

ELECTRICAL/CONTROLS

- 2400VA maximum
- 120VAC input
- Suitable for dry location only



LISTING

- ETLus listed to Track Lighting Systems UL 1574
- cETL listed to Track Lighting Systems CSA C22.2#250.570

TRACK ACCESSORIES



020




099

SERIES	350	Zonyx
TYPE	020 099	end cap bending machine
FINISH	MC	matte chrome

ORDERING CODE _____

Follow the steps to specify your fixture, example:
350 - 004 - MC

ZONYX CONNECTORS



060, 061




065


SERIES	350	Zonyx
TYPE	060 061 062 063 064 065	conductive track connector iso track connector L-connector cross connector T-connector flexible track connector
FINISH	MC	matte chrome

ORDERING CODE _____


Follow the steps to specify your fixture, example:
350 - 062 - MC



064



063



062

ZONYX MOUNTING


SERIES	350	Zonyx
TYPE	100	120° suspension support
	110	4" ceiling support
	120	7-1/2" - 11-1/2" adjustable ceiling support
	130	14-1/4" - 24" adjustable slanted ceiling support
	150	5-1/2" - 8-1/2" wall support I
155	14" - 24" wall support II	
FINISH	MC	matte chrome

ORDERING CODE

Follow the steps to specify your fixture, example:
350 - 120 - MC




110




120




100



130




150




155

ZONYX POWER SUPPLY



115



125



105

SERIES	350	Zonyx
TYPE	105 115 125	10 ft cable power feed** 4" canopy power feed 7-1/2" - 11-1/2" adjustable power stem*
CIRCUIT BREAKER	010 020 030 050 075 125	1 amp breaker 2 amp breaker 3 amp breaker 5 amp breaker 7.5 amp breaker 12.5 amp breaker
FINISH	MC	matte chrome

ORDERING CODE _____

Follow the steps to specify your fixture, example:
350 - 125 - MC - 020

CURRENT LIGHTING CIRCUIT BREAKER

The power feed circuit breaker limits the allowable electric load that can be put on the circuit. This device may be used to meet applicable energy codes including California Title-24.

TECHNICAL SPECS

- 2400VA maximum
- 120VAC input
- Suitable for dry location only
- Mount to 3" - 4" round J-box
- Switchable circuit breaker (1 - 25A)

*extendable from 13.88" - 24"

**can be field shortened